



SPIDER 2SGS – Technical Datasheet

Remote-controlled slope mower

Compact remote-controlled slope mower designed for professional maintenance of extreme slopes and hard-to-reach areas.

Ensures maximum safety, high productivity, and excellent terrain accessibility.



Specification	2SGS FS	2SGS EFI	2SGS SUPER LOW
Engine	Kawasaki FS691V	Kawasaki FS730V EFI	Kawasaki FS730V EFI
Performance	24 HP / 17.9 kW	25.5 HP / 19 kW	25.5 HP / 19 kW
Displacement	726 ccm	726 ccm	726 ccm
Fuel Tank	4.2 gal	4.2 gal	4.2 gal
Fuel	Unleaded gasoline	Unleaded gasoline	Unleaded gasoline
Drive System			
Transmission	Hydrostatic	Hydrostatic	Hydrostatic
Oil Tank	2.4 gal	2.4 gal	2.4 gal
Speed	0–5 mph	0–5 mph	0–5 mph
Drive	360° 4-wheel drive	360° 4-wheel drive	360° 4-wheel drive
Skid-Steering	Yes	Yes	Yes
Tire Type	16 × 6.50–8	16 × 6.50–8	16 × 6.50–8



SPIDER 2SGS – Technical Datasheet

Specification	2SGS FS	2SGS EFI	2SGS SUPER LOW
Performance			
Productivity	Up to 1.73 acres/hr	Up to 2.1 acres/hr	Up to 2.1 acres/hr
Fuel Consumption	0.95 gal/hr	1 gal/hr	1 gal/hr
Climbing Ability (no winch)	up to 41°	up to 41°	up to 35°
Climbing Ability (with winch)	up to 55°	up to 60°	-
Hydraulic Winch	Yes	Yes	No
Dimensions (L×W×H)	65 × 56 × 32.5 in	65 × 56 × 32.5 in	65 × 56 × 28 in
Gross Weight	853 lbs	853 lbs	794 lbs
Cutting System			
Cutting Width	48.5 in (4 blades)	48.5 in (4 blades)	48.5 in (4 blades)
Cutting Height	2.5 – 5.5 in. / 1 – 3 in.	2.5 – 5.5 in. / 1 – 3 in.	5.5 in.
Blades	4 mulching blades	4 mulching blades	4 mulching blades
Clutch	Electromagnetic	Electromagnetic	Electromagnetic
Remote Control			
Range	up to 328 ft (100 m)	up to 328 ft (100 m)	up to 328 ft (100 m)

Interested? Contact us for demo & pricing

sales@spidermowerusa.com

www.spidermowerusa.com